

Eva CK DF

Purely Soft Water



Eva CK DF

Eva CK DF is a range of softeners assembled with the Pollet Water Group exclusive Eva cabinet. Controlled by an interactive and intelligent valve, the Eva CK DF is an economical and user-friendly unit to install and service. Eva CK DF softeners are available from stock in 5 different sizes and 3 different colours.

FEATURES



PWG EXCLUSIVE
cabinet



CLEAN LOOK
with glossy cover



SMALL FOOTPRINT



USER FRIENDLY
Handles for easy moving



EASY SALT FILLING
due to tilting salt lidt



THREE SIZES
Mini, Midi & Maxi



TRANSPARANT WINDOW
good visibility valve

COLOURS





COMPOSITION

The Eva CK DF softeners come with:

- Pallas CK electronic downflow meter valve
- Eva Tilting Lid Cabinet
- Composite vessel with distributor & tube
- Heterodisperse resin
- Bypass WS1
- Brine well & safety brine valve 2310

Note: The configuration as mentioned above is available from stock.
For personalised units, please contact us for more information on price and delivery time.

ORDER REFERENCE	ITEM NAME	DIMENSIONS (W X D X H) IN MM
MINI		
4201050005	Eva CK DF Mini 10L	300 x 500 x 741
4201050006	Eva CK DF Mini 14L	300 x 500 x 741
MIDI		
4201050007	Eva CK DF Midi 18L	300 x 500 x 1072
MAXI		
4201050008	Eva CK DF Maxi 22L	300 x 500 x 1200
4201050009	Eva CK DF Maxi 30L	300 x 500 x 1200

FEATURES CONTROLLER

- **Backlight multi colour screen**
Display changes colour to indicate installation status
- **Service indication**
Your company name & phone number on the screen
- **Proportional brining**
Significant reduction in the salt consumption
- **Low salt alarm**



TECHNICAL SPECIFICATIONS SOFTENER

MODEL	MINI		MIDI	MAXI	
Dimensions mm (H x W x D)	741 x 300 x 500		1072 x 300 x 500	1200 x 300 x 500	
Exchange capacity (kg CaCO ₃)	0,38	0.45	0.86	1.12	1.54
Control System	Pallas CK		Pallas CK	Pallas CK	
Regeneration type	Downflow		Downflow	Downflow	
Tank Size	8x17	10x17	8x35	8x35	10x35
Unit Size	10	14	18	22	30
Service Flow Rate (m ³ /h)	0.9	1.2	1.5	1.8	2.4
Peak Flow Rate (m ³ /h)	1.9	2.9	1.9	1.9	2.9
Water Used / Regeneration (L)	55	83	86	97	132
Plumbing Connections	1"		1"	1"	
Electrical Rating	220V/50Hz		220V/50Hz	220V/50Hz	
Water Supply	Municipal		Municipal	Municipal	
Water Temperature	4 - 43°C		4 - 43°C	4 - 43°C	
Operating Pressure	1,4 - 8,6 bar		1,4 - 8,6 bar	1,4 - 8,6 bar	