



Jane Ino

Intuitive. Versatile. Efficient.

Jane Ino

Tailored to your needs, the Jane Ino is an exclusive all-round softener. The versatile integrated controller has an intuitive programming and is easy to service.

FEATURES SOFTENER

ATTRACTIVE DESIGN



INTEGRATED TIMER



EXCELLENT COMBINATION
matt body & shiny cover



SMALL FOOTPRINT



ROBUST
strong & durable cabinet



USER-FRIENDLY



INTUITIVE PROGRAMMING



ERGONOMIC HANDLES
To easily move the unit



PRACTICAL
Tilting salt lid



EASY CONNECTION
Between valve & timer

PERFORMANCE

- 3
THREE SIZES
 Mini, Midi & Maxi
- 
REGENERATION
 4 programmable
 regeneration displays
 proportional brining



PREDEFINED CONFIGURATION



2 STANDARD COLOUR COMBINATIONS

- BLACK CABINET, BLACK COVER & GREY SALT LID
- WHITE CABINET, WHITE COVER & GREY SALT LID

*standard color cabinet: white or black, cover: white or black, salt lid: grey

FEATURES CONTROLLER



UNIQUE CONTROL VALVE TECHNOLOGY

Hydraulic valve body & electronic controllers

INTUITIVE

Easy programming

EASY MAINTENANCE

Thanks to the design of the valve

RELIABLE

In-house PWG Manufacturing

EUROPEAN PRODUCTION

Made in France

TECHNICAL SPECIFICATIONS SOFTENER

MODEL	MINI		MIDI	MAXI	
Dimensions mm (H x W x D)	741 x 300 x 500		1072 x 300 x 500	1200 x 300 x 500	
Exchange capacity (kg CaCO ₃)	H 0.40 M 0.45	H 0.56 M 0.63	H 0.75 M 0.79	H 1.09 M 1.15	H 1.47 M 1.55
Control System	Ino 20		Ino 20	Ino 20	
Regeneration type	UPR*		UPR*	UPR*	
Tank Size	8x17	10x17	8x30	8x35	10x35
Unit Size	10	14	18	22	30
Service Flow Rate (m ³ /h)	0.7	1.0	1.3	1.5	1.7
Peak Flow Rate (m ³ /h)	1.6	2.4	1.6	1.6	2.1
Water Used / Regeneration (L)	31.5	70.5	60.6	73.6	118.6
Plumbing Connections	3/4" or 1"		3/4" or 1"	3/4" or 1"	
Electrical Rating	220-240V 50HZ		220-240V 50HZ	220-240V 50HZ	
Water Supply	municipal		municipal	municipal	
Water Temperature	1 to 45°C		1 to 45°C	1 to 45°C	
Operating Pressure	2 bars		2 bars	2 bars	

UPR* : Upflow Regeneration

Join our mission.
Make water count.