

UV 405 LCD² Technical Data

GENERAL INFORMATION	
Max flow rate	19 l/m
UVC transmittance	99%- 1 cm
UVC dose	300 J/m ²
Water Temperature range	5-50° C
Total consumption	33 W
Mounting	Vertical or horizontal

UV REACTOR	
Material	Stainless Steel 304 (optional 316L)
Connections	Thread ¾" M
Total Volume	1 l
Total weight	1.5 kg
Max working pressure	10 bars g
Protection class	IP 54
Shape	U
Flow direction	From bottom to top


UV LAMP	
Number	1
Lifespan	9000 hr
Lamp power	30 W
Type	Low pressure type 028102

UV SENSOR (ONLY on PLUS MODELS)	
Type	UVC selective sensor Mod. UV73S/TF
Sensor Cable	Shielded cable 4 meters
Sensor holder material	Teflon


CONTROL PANEL	LCD (PLUS)
Material and colour	Black Polypropylene
Dimensions	215 x 215 x 90 mm
Protection class	IP 55 (IP 65 on request)
Ambient temperature range	5 – 45 °C
Power supply	230 V - 50/60 Hz (115V – 50/60 Hz on request)
Lamp cable	1 m
Power supply cable	1 m
Monitor display	LCD SITA
Hour meter	Yes for total system life
Resettable hour meter	Yes for lamp life control
Lamp function control	Yes
Alarm led	Yes
Free contact (NO - NC)	Yes – general alarm (max 2 A)
230 V output (NO - NC)	Yes – general alarm (max 2 A)
Remote ON/OFF contact	Yes (settable)
ON/OFF Timer	Yes (settable)
Reactor temperature measurement and alarm	Yes (°C) – settable value (shut off for high temperature) on PLUS MODELS
UV Irradiance measurement and alarm	Yes (% or W/m ² optional) – settable value on PLUS MODELS
4/20 mA output	Optional – for Irradiance and water temperature on PLUS MODELS
Audio alarm	Optional

Rev. 02-2021


IRRADIATION SENSOR COUPLING
ONLY FOR PLUS VERSION



UV 405 LCD CONTROL



UV 412 LCD CONTROL



IRRADIATION SENSOR COUPLING
ONLY FOR PLUS VERSION

NOTA:

- LE DIMENSIONI DI INGOMBRO INDICATE SONO SUSCETTIBILI DI MINIME VARIAZIONI DOVUTE ALLE TOLLERANZE COSTRUTTIVE E DI ASSEMBLAGGIO DEI COMPONENTI MECCANICI IMPIEGATI

NOTE:

- THESE OVERALL DIMENSIONS CAN CHANGE A LITTLE BECAUSE OF THE CONSTRUCTIVE TOLERANCES AND THE ASSEMBLING OF MECHANICAL COMPONENTS YOU USED.

NOTE:

- CES TOTALES DIMENSIONS PEUVENT SUBIR DES MOINDRES MODIFICATIONS POUR LES CONSTRUCTIVES TOLERANCES ET L'ASSEMBLAGE DES MECANQUES ELEMENTS UTILISES.

* _BULLONE M4 PER
MESSA A TERRA
_EARTHING BOLT

NOME FILE: UV405-412 LCD.DWG

A	PRIMA EMISSIONE	30/10/14		SCHENONE	MAZZONE
REVISIONE	DESCRIZIONE	DATA		DISEGNATO	APPROVATO
 S.r.l. Società Italiana Trattamento Acque Via Rivarolo, 61 - 16161 Genova Italy - Tel. 0039-10-7406848 / Fax 0039-10-7406851 email info@sitaouv.com		TITOLO		CODICE	
		DISINFEZIONE UV-C		/	
		MODELLO 405 - 412 LCD		F.to	Scala
		LAY-OUT		A4	/
		CLIENTE		Foglio	di
		/		01	01

LA SITA s.r.l. SI RISERVA A TERMINI DI LEGGE LA PROPRIETA' DI QUESTO DISEGNO CON DIVIETO DI RIPRODURLO O DI RENDERLO COMUNQUE NOTO A TERZI O A DITTE CONCORRENTI SENZA LA SUA AUTORIZZAZIONE SCRITTA