

Pallas[®]
RO



Pallas[®]

RO

Pallas residential & commercial RO's improve the water quality by removing minerals such as sodium, sulphate, chlorine, sediment and bacteria. Better water not only influences your devices, but also the taste of your coffee, your tea, your ice. The domestic & commercial solutions provided by the Pollet Water Group improve your day-to-day life and ease your comfort. Our new Pallas RO range is manufactured inhouse in compliance with the industry's standard and norms.





ADVANTAGES OF PALLAS RO'S

- + Short payback time
- + No more bottles of water:
 - + No handling of heavy packaging
 - + Less waste
 - + No stock of bottles needed
- + Water filtration up to 1/1000 μ with removal of:
 - + Chlorine taste
 - + Smell
 - + Heavy metals
 - + Bacteria
 - + Viruses
- + 24h/24h clear and pure water
- + Plug & Play systems
- + Compact unit
- + Sustainable
- + Low carbon footprint (No transport of water)
- + Better taste of your coffee and tea
- + Perfectly suitable for ironing
- + Private & white label possibilities
- + Different colour options based on MOQ

Pallas®

Enjoy Slim Digital

5 Stage reverse osmosis system
with pump (available for EU or UK).



Features

- Direct flow 400 GPD
- Digital screen
- With pump (EU or UK)
- Quick connection RO unit
- Installation kit

USP's

- The best option for removing PFAS from drinking water, ensuring it meets safe limits
- In-house manufacturing
- Digital real-time view of operation
 - Conductivity of treated water
 - Lifetime filters & membrane
 - Status: working or alarm
- Most advanced filtration system for point of use
- Compact design, easy to install
- Direct flow (1.1 l/min.)
- Optional storage tank



Dimensions & weight

- Dimensions (cm): 35 x 48 x 46
- Weight : 11,5 kg



Key components

- 12" Pallas Inline HND Sediment Filter
- 12" Pallas Inline HND Granular Active Carbon (GAC) Filter
- 12" Pallas Inline HND Carbon Bloc Coconut (CTO) Filter
- 10" Pallas Inline HND Post Carbon Coconut Filter
- 2 x 200 GPD Membrane in direct flow (with pump)
- Metallic Ball Valve 3/8"
- 400GPD Pump
- Transformer 24V 3A
- RO Faucet

Technical specifications

Capacity	400 GPD - 1 LPM
Recovery	45-50%
Rejection	>96%
PFAS rejection	99%
Type	Direct flow
Membrane	2 x 200 GPD Pallas
Pump	24V
Prefiltration	3 stage PP - CTO - GAC
Post filter	Yes – Stabilizer
System flush	Yes
Storage tank	Optional
Leak detector	Yes
Faucet	SS 304 Lux faucet incl.
Connection type	Quick

Pallas[®]
RO

Make water count.

www.polletwatergroup.com/pallas